

Wall-mount Remote Control – 2-buttons

Product ref.: 140665A0



Product features

- Flexible wall-mount remote control with two channels for central control of Homematic IP devices
- Can be used e.g. for switching lights on and off or for activating and deactivating the eco mode
- Can be flexibly mounted with supplied adhesive strips or screws
- Easy to integrate into existing switches with 55 mm frames of the following manufacturers: Berker, Busch-Jaeger, GIRA, Merten, JUNG, Kopp and ELSO
- To enable operation, the device has to be connected with one of the following solutions:
 - Homematic IP Access Point with free smartphone app and free cloud service
 - Central Control Unit CCU2/CCU3 with local user interface WebUI
 - Third-party solutions of partners

Technical specifications

Supply voltage	2x 1.5 V LR03/Micro/AAA
Current consumption	50 mA max.
Battery life	4 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	without frame: 55 x 55 x 17 mm incl. frame: 86 x 86 x 19 mm
Weight	82 g (incl. batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typ. open area RF range	200 m

Logistical data

Product reference	140665A0
EAN code	4047976406654
Short description	HMIP-WRC2
Packing unit	90
Packing dimensions	122 x 112 x 48 mm
Weight incl. packaging	195.0 g

Package contents

Homematic IP Wall-mount Remote Control – 2-buttons

Clip-on frame

Mounting plate

Double-sided adhesive strips (2x)

Screws 3.0 x 30 mm (2x) and plugs 5 mm (2x)

1.5 V LR03/Micro/AAA batteries (2x)

User manual