


SAVES UP TO 30 %
ON ENERGY – IN THE
OFFICE OR AT HOME

Radiator Thermostat – compact

HmlIP-eTRV-C-2

The radiator thermostat with extra long battery lifetime: Saves up to 30% on energy consumption and reduces the CO2 emissions thanks to individual heating profiles and connected window contacts. With its tamper-proof design, the radiator thermostat is suitable especially for public buildings and small businesses.



homematic 
Smart Living, Simply Exciting.



SAVES HEATING COSTS

Individual temperature profiles can easily be created via the app – with up to 3 configurable heating profiles and 13 changes per day. In this way, the heating is switched on only if needed. And during ventilation, the room temperature is automatically reduced thanks to the open-window function.



Individual heating profiles via the free Homematic IP app



To enable operation, the device has to be connected with one of the following solutions:

- Homematic IP Access Point with free smartphone app and free cloud service
- Central Control Unit CCU2/CCU3 with the local user interface WebUI
- Third-party solutions of partners

TECHNICAL SPECIFICATIONS

Supply voltage	2x 1.5 V LR6/mignon/AA
Current consumption	100 mA max.
Battery life	5 years (typ.)
Degree of protection	IP20
Ambient temperature	0 to 50 °C
Dimensions (W x H x D)	51 x 98 x 48 mm
Weight	172 g (including batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typical open area RF range	250 m
Threaded connection	M30 x 1.5 mm

SAFE AND EASY TO MAINTAIN

Ideal for application in offices, medical centres, small enterprises or children's rooms. The closed housing design prevents from unwanted operation or manipulation. Operation and settings are realised only via the Homematic IP app, a wall thermostat or via voice control with Amazon Alexa or Google Assistant. The device is secured additionally by the disassembly protection supplied. Thanks to the long battery life of 5 years (typically), the radiator thermostat requires minimal maintenance.

OPEN-WINDOW DETECTION

The Homematic IP Window and Door Contact offers exact detection of open windows and doors. The room temperature is automatically reduced to avoid any waste of energy.

SECURE AND EASY INSTALLATION

High-quality metal nut for secure installation to standard radiator valves with M30 thread size. Quick and easy installation without having to drain any water or intervening in the heating system. The flat housing also allows installation under mounting conditions where space is limited.

MANY ADDITIONAL FUNCTIONS

- ✓ Whisper mode for quiet operation even in bedrooms
- ✓ Boost function via the app for quick heating of rooms
- ✓ Eco mode for energy-saving operation with reduced room temperature
- ✓ Valve protection function against calcification of the valve



incl. disassembly protection

LOGISTICAL DATA

Product reference	155648A0
EAN code	4047976556489
Short description	HmlIP-eTRV-C-2
Packing unit	45
Packing dimensions	122 x 112 x 97 mm
Weight incl. packaging	318.0 g

PACKAGE CONTENTS

Homematic IP Radiator Thermostat – compact
 Homematic IP Disassembly Protection
 Adapters Danfoss (RA, RAV and RAVL)
 Mounting accessories
 Square key
 1.5 V LR6/mignon/AA batteries (2x)
 User manual